



A HISTORY OF BEING AHEAD OF OUR TIME

PRODUCT DESCRIPTION: SAFETY SCRAPE Product # 400

GENERAL SPECIFICATIONS:

SURFACE:	Type:	100% Nitrile Rubber (15% recycle content)
BACKING:	Type:	100% Nitrile Rubber (15% recycle content)
	Thickness:	3/8"
	Color:	Black

FEATURES:

- Molded rubber pattern on face provides traction under wet conditions and scrapes heavy soil from shoe soles.
- Gripper backing enhances traction to floor.
- Heavyweight keeps mat in place.
- Nitrile rubber construction allows for use in environments that are exposed to animal fats and petroleum products.
- Provides some anti-fatigue properties.
- Available with OSHA Safety Borders in yellow, orange, green, and red.
- Use in kitchens, locker rooms, restaurants, production areas, outside entrances, and grocery store produce areas.
- ANSI/ESD 57-1 1994 Protection of Electrostatic Discharge of Susecptible Items: Flooring Materials
 - Surface to Ground - 4.3×10^5 ohms @ 50% Relative Humidity
 - 4.6×10^5 ohms @ 12% Relative Humidity
 - Surface to Surface - 1.8×10^6 ohms @ 50% Relative Humidity
 - 1.8×10^6 ohms @ 12% Relative Humidity
- Passes Flammability Standard DOC-FF-1-70
- Static Decay Test Method 4046 Federal Standard 101B/NFPA 99 Chapter 12 Section 4.1.3.8 (f) (3) (i) Maximum Time Recorded: .01 seconds.
- ASTM C1028-96 Static Coefficient of Friction: Dry - .74
- U.V. Stable